

Amend the drawings, to correct and add cross hatch markings in Figs. 1, 4, 5, 7, 9, 10, 11, 12, 13, 14, 16, 18A, 18B, 18C, 19A, 19B, 19C, 21, 22, 23, 24A, 24B, 24C, 25A, 25B, and 25C, as follows, and as marked in red on the attached copy of these drawings.

Fig. 1 - replace screen hatching with metal hatching for element 14, and add resin hatching to elements 20, 32a-32g.

Fig. 4 - same as Fig. 1 for elements 14 and 20, and add resin/ plastic hatching to elements 32a-32f.

Fig. 5 - elements 14, 20 same as Fig. 1, and add resin/ plastic hatching to elements 32a-32f.

Fig. 7 - elements 14, 20 same as Fig. 1, and add resin/ plastic hatching to elements 32a-32e.

Fig. 9 - same as Fig. 7.

Fig. 10, 11, 12, 13, 14, 16, 18A-C, 19A-C, 21, 22, 23, 24A-C, 25A-C - add resin/ plastic hatching to elements 20, 22a-b, 32a-e as they appear, and add semi-conductor cross hatching to element 40 as it appears.

Figs. 13, 14, 15 - add the legend PRIOR ART.

Support for the selection of materials resides in the specification. No new matter has been added.

Substitute Formal Drawings:

Applicant hereby submits, for the Examiner's and the Chief Draftsman's approval, a substitute copy of the formal drawings, sheets 1-18, Figs. 1- 25C, with the above-cited amendments in place.

In the Specification:

Page 1, line 32, change "24a" to - - 12a - -.

Page 1, line 33, change "24b" to - - 12b - -.

Page 3, line 8, change "shirt-circuit" to - - short-circuit - -.